

# MEDIUM-DUTY PULLERS

## Medium Duty Belt Pullers, Wheel Pullers & Embossers

- PERFECT FOR SMALL TO MEDIUM SIZE EXTRUSIONS.
- EASY TO USE, WITH CONVENIENTLY MOUNTED CONTROLS.
- BELT PULLERS FEATURE NON-MARKING POLY "V" BELTS FOR CLEAN CONTACT WITH EXTRUDATE.
- WHEEL PULLERS UTILIZE RUBBER COVERED PULLER WHEELS. IDEAL FOR WIDE OR DIFFICULT TO GRIP EXTRUSIONS.
- WHEEL PULLERS AND EMBOSSERS AVAILABLE AS SINGLE STAND, TWO SHAFT OR DOUBLE STAND, FOUR SHAFT UNITS.



Increased Productivity Starts Here

# SPECIFICATIONS

## MEDIUM DUTY BELT PULLERS

| MODEL                | 230-6                            | 240-6 | 248-6 |
|----------------------|----------------------------------|-------|-------|
| Belt Drive           | 2 HP A.C.                        |       |       |
| Belt Height          | 42" ± 2"                         |       |       |
| Max Belt Opening     | 6"                               |       |       |
| Belt Contact Length  | 30"                              | 40"   | 48"   |
| Belt Width           | 6"                               |       |       |
| Belt Speed (FPM)     | Customer specified               |       |       |
| Power Supply         | 208-230/3/60 (optional 460/3/60) |       |       |
| Floor Dimensions     | L                                | 46"   | 64"   |
|                      | W                                | 26"   |       |
| Typical Applications | Automotive and building products |       |       |

## WHEEL PULLERS & EMBOSSERS

| MODEL                           | 202                                     | 204 | 302         | 304 |
|---------------------------------|---|-----|-------------|-----|
| Wheel/Roll Drive                | 1HP AC                                  |     |             |     |
| Wheel/Roll Height               | 42" ± 2"                                |     |             |     |
| Number of Wheels                | 4                                       | 8   | N/A         |     |
| Wheels                          | 10" OD 2" Face Width,<br>Rubber Covered |     | N/A         |     |
| Wheel Opening                   | 0 - 4"                                  |     | N/A         |     |
| Embossing Stands                | N/A                                     |     | 1           | 2   |
| Embossing Roll Diameter         | N/A                                     |     | 5" - 12" OD |     |
| Max. Product Width              | 18"                                     |     |             |     |
| Line Speed Without Transmission | 10 -100 FPM or other 10:1 speed range   |     |             |     |
| Line Speed With Transmission    | 1/2 - 80 FPM, 1-160 FPM, 2-320FPM       |     |             |     |
| Power Supply                    | 208-230/3/60 - 400/3/60                 |     |             |     |

**A wide variety of options are available.**

Specifications subject to change without notice.



160 Covington Drive  
 Bloomingdale, IL 60108  
 PHONE: 630-893-4500  
 FAX: 630-893-5010  
 www.rdnmfg.com